

Original Research Article

Removal of heavy metals Cd (II), Fe (III) and Ni (II), from aqueous solutions by natural (clinoptilolite) zeolites and application to industrial wastewater

ABSTRACT (ARIAL, BOLD, 11 FONT, LEFT ALIGNED, CAPS)

The adsorption mechanism of Cd, Fe, and Ni, ions on natural (clinoptilolite) zeolites, a regional low-cost naturally available adsorbent, was studied, in a batch adsorption system. The effect of several parameters such as contact time, zeolite dose, particle size, effect of pH, and initial concentration of metal ions on the adsorption process was estimated. The optimum adsorption was found to occur at pH 6.0, adsorbent dose 1.0 g/L, and initial concentration 2, 20 and 10 mg/L for Cd, Fe, and Ni, respectively. The adsorption efficiency also, increases with decreasing particle size of zeolites and the effect of retention time on adsorption ratio shows that 80% of the Cd, Fe, and Ni, are adsorbed by Zeolite during early 120 minutes. Under these optimum conditions, the removal efficiency was 78.8 %, 89.1%, and 65.5% of Cd, Fe, and Ni, ions, respectively. Sorption data have been interpreted in terms of Langmuir and Freundlich isotherms. The adsorption efficiency of heavy metals in industrial wastewater as application mode, was also, investigated using zeolites and these results show that natural zeolites hold great potential to remove cationic heavy metal species from industrial wastewater and confirms the potential use of zeolite for the removal of heavy metals from industrial wastewater via adsorption. It is concluded that zeolites is very promising for the removal of metal ions from aqueous solution and hence may be encourage the utilization of zeolites in environmental applications.

decrease medical as well as financial burden, hence improving the management of cirrhotic patients. These predictors, however, need further work to validate reliability.

Keywords: *Natural (clinoptilolite) zeolites, Adsorption, Heavy metals, Industrial wastewater.*

1. INTRODUCTION

Environmental pollution by heavy metals has led to serious problems for humans and other organisms in the environment due to their nonbiodegradability and accumulation in the living organisms [1]. The main sources of these heavy metals into the ecosystem through wastewater streams are electroplating, smelting, paint pigments, batteries, mining operations and agriculture sector [2]. Nowadays, removing the toxic heavy metal contaminants from aqueous waste streams is one of the greatest matters of interest in the literature and studies. The main concern of environmentalists about heavy metals is that these elements are highly toxic and their detrimental impact on human health and surroundings is grave [3]. Heavy metal removal from aqueous solution is one of the most pressing environmental problems throughout the world these days. In the recent years, the removal of heavy metals from industrial wastewater has been inclusively investigated. Conventional methods including, electrodialysis [4], chemical precipitation [5], reverse osmosis [6], ion-exchange [7], ultrafiltration [8], and adsorption are used for removal of heavy metal ions from aqueous solutions. While most of these techniques are expensive and inapplicable on a large scales, ion exchange and adsorption method, among all above-mentioned processes, is the most preferable one because it is economically advantageous, highly efficient and applicable [9,10]. Ion exchange and adsorption is one of the few promising alternatives for this purpose, especially using low-cost natural sorbents such as clay materials, zeolite, biomass, perlites and diatomites. In this regard naturally occurring zeolites hold great potential to be used as packing material in subsurface reactive barriers intercepting ground water plumes, and for fixed bed reactors designed to remove heavy metals from industrial wastewater [11]. Zeolites have a framework silicate with a three-dimensional cage structure. Their structure bears negative charges which can be balanced by adsorption of exchangeable cations [12]. Due to high deposit of Zeolite in nature, and to its low cost, strong adsorption capacity, it has recently drew

attention to be used in the treatment of industrial wastewater. Zeolites are crystalline aluminosilicates enclosing pores occupied by cations and water molecules, permitting reversible ion exchange and reversible dehydration [13]. The cationic makeup of the aluminosilicate consists of aluminum ions (Al^{3+}) in a predominantly Si framework (an aluminosilicate). The charge imbalance resulting from the substitution of aluminum atoms for silicon atoms requires a nearby cation to preserve electrical neutrality, so the cation content is directly related to the Al content. In nature, these cations are typically alkaline earth elements such as Na^{+1} , Ca^{+2} , Mg^{+2} and metal ions. Zeolites can provide adsorption sites with exchangeable cations for heavy metal ions and porosity for free metals, with ion exchange and molecular adsorption being the main mechanisms, respectively [14]. The process of adsorption is now widely accepted, very effective and economically viable to be used to remove heavy metal ions in industrial waste as well as in drinking water. Besides ion exchange and adsorption, the other mechanisms indirectly involved during heavy metal removal from aqueous solutions via zeolites are surface precipitation and destruction of clinoptilolite structure (i.e. dissolution of the clinoptilolite framework cations) [15]. A wide variety of heavy metals can be removed from the liquid phase at significant quantities and kinetics is usually fast. The fact that zeolite exchangeable ions are relatively innocuous (sodium, calcium and potassium ions) makes them particularly suitable for removing undesirable heavy metal ions from industrial effluent waters. The high selectivity for toxic metals such as Pb, Cd, and Zn makes clinoptilolite a promising material for treatment of different type of wastewaters. The safety of using natural Zeolite is attributed to the non-toxicity of its metals that displace unfavorable toxic heavy metals from wastewater in the desalter.

Zeolite is structurally stable even at acidic environment that can be easily reproduced with some modification to improve its structure and adsorption capacity. Due to these attracting properties of Zeolite, interest has been increased towards the method of heavy metal adsorption from aqueous solution. Many studies reported the importance of using natural Zeolite for the adsorption of heavy metals under different empirical conditions such as temperature, pH, concentration, granular phase volume, and induction speed [16 - 20].

In the present study natural Zeolite was tested as an efficient adsorbent for the removal of ions of Cd, Fe and Ni, from aqueous solutions and wastewater. This article aims to investigate the parameters that affect removal rate i.e. contact time, particle size, pH of initial solution and zeolite dose, determination of maximum adsorption capacity of natural Zeolite which is used to remove the studied metal ions through equilibrium reactions, comparing the empirical data of adsorption balance with Langmuir and Freundlich sorption models in order to evaluate the adsorption performance of natural Zeolite.

2. MATERIAL AND METHODS

2.1 Preparation of Materials

Analytical grade chemicals were employed in all experiments. The compounds, $Cd(NO_3)_2 \cdot 4H_2O$, $FeCl_3 \cdot 6H_2O$ and $Ni(NO_3)_2 \cdot 4H_2O$, were purchased from Sigma Aldrich (USA) and used in the experiments. Appropriate amounts of the metal salts were dissolved in mega-pure or de-ionized water (DIW) to yield the stock solutions of concentration 1000 mg/L. The stock solutions were further diluted with DIW water to obtain the various concentrations used in the adsorption studies. All glassware were thoroughly washed with soap, followed by 10 % HNO_3 and then rinsed many times with DIW before use. The adjustment of pH was done using either 0.1 M HNO_3 or 0.1M NaOH, and pH was measured with a pocket pH meter model Orion 210. Natural zeolite from Alex Trading & Commercial Agencies Company was used. The grain size fractions were used as received from the company in two Size: <0.5 mm (fraction I), 2.0 – < 6mm (fraction II).

2.1.1 Characterization

The main chemical composition of zeolite analyzed by X-ray diffraction(XRD) and X-ray fluorescence(XRF) methods, as well as other Physical properties such as particle size, density, humidity, fire loss, water, porosity, surface area, and hydrogen ion concentration carried at Central Metallurgical Research Institute (CMRDI).

90 2.1. 2 Industrial wastewater

91 Industrial wastewater samples were collected, from collected industrial wastewater treatment plant
92 from Adabiya area at Suez bay, Egypt. Two main samples form inlet and outlet of this plant were
93 collected, and then stored in acid-washed polyethylene bottles for analysis. All the precautions
94 recommended by [21], to minimize risks of sample contamination were followed during collection and
95 treatment of samples.

96 2.2 Batch Adsorption Studies

97 To evaluate the process of single adsorption of Cd, Fe, and Ni from aqueous solution, different
98 parameters and factors were studied. The aqueous solutions were agitated at different time intervals
99 in a room temperature and on a mechanical shaker at 200 rpm. After the reactions, the supernatant
100 was collected by a syringe and filtered through a 0.2µm membrane filter to measure the metal ions
101 concentrations using a flame atomic absorption spectroscopy (Perkin Elmer A Analyst 100). Samples
102 were diluted before the required analysis to set the calibration linear range.

103 2.2.1 Effect of pH

104 In order to investigate the optimum pH of adsorption, 50 ml of aqueous solution containing 2 mg/l of
105 single metal ions (Cd, Fe, and Ni) and having pH range from 2 to 8 were mixed with 0.5 g of
106 adsorbent in a 250 ml conical flask. After 180 min of contact time, the suspension were filtered and
107 analyzed for heavy metal ions by atomic-adsorption spectrophotometer.

108 2. 2. 2 Effect of Adsorbent Dosage

109 Furthermore, to evaluate the optimum dosage of the, adsorbent dose studies were carried out with
110 0.25, 0.5, 0.75, 1, 1.5, 2 and 4.0 g adsorbent and 50 mL of solution containing 2 mg/l of heavy metal
111 ions concentrations at optimum pH obtained from section above during the contact time of 180 min at
112 room temperature.

113 2. 2. 3 Effect of particle size

114 In order to investigate the grain size effect of zeolite, the batch experiment was performed in two
115 sizes: < 0.5 mm (fraction I), 2.0 – < 6mm (fraction II). In these experiments, 50 mL of solution
116 containing 2 mg/l of heavy metal ions concentrations at optimum pH and adsorbent dose , the contact
117 time of 180 min at room temperature.

118 2.2.4 Effect of initial heavy metal ions concentration

119 The kinetic study for metals was also performed using different concentrations (1.0, 2.0, 5.0, 10.0,
120 20.0, 50.0, 100.0 mg /l) of each single metal ion. Optimum conditions such as pH and adsorbent dose
121 determined previously in the batch studies were applied for this batch studies.

122 2.2.5 Effect of contact time

123 The time-dependent behavior of Cd, Fe, and Ni adsorption was also studied by varying the contact
124 time between the adsorbate and the adsorbent at 5, 15, 30, 60, 90, 120, and 180 min at room
125 temperature. The optimum conditions of solution such as pH, adsorbent dose, and metals
126 concentrations determined previously in the batch studies were used to determine the effect of
127 contact time on the adsorption behavior of zeolite.

128 2.3 Equilibrium

129 The main objective of the equilibrium studies was to determine the maximum capacity of natural
130 zeolite towards Cd, Fe, and Ni removal under the studied conditions and according to make a
131 selectivity comparison for these. Experimental data were fitted to conventional adsorption
132 mathematical models. These were used to predict the adsorption performance of natural zeolite.

133 Adsorption capacity formula is given in the following equation: $q_e \text{ (mg/g)} = \frac{x}{m} = \frac{(C_i - C_e) \times V}{m}$,
134 where q_e is the quantity of dissolved absorbed material in mg per g of the adsorbent at equilibrium,
135 C_i : initial concentration of contaminant in solution at equilibrium (mg/l), V : volume of water phase (l),

M: mass of solid phase (g). Percentage of metal removal can also be displayed by the percentage of metal removal as follows: Metal removal (%) = $100 (C_0 - C_e) / C_0$.

2. 3. 1 Langmuir Adsorption Isotherms

Langmuir model suggests that adsorption occurs on monolayer of the surface which contains unlimited number of adsorption sites of equal energy. Linearity of Langmuir equation is expressed as

follows: $\frac{C_e}{q_e} = \frac{1}{q_0 b} + \frac{C_e}{q_0}$. Where q_0 is the maximal adsorption capacity at the surface availability of binding sites (mg/g), b is Langmuir constant which is related to the radical energy of adsorption, b and q_0 can be extrapolated from the slope of linear plot of $\frac{C_e}{q_e}$ with index of C_e [22, 23].

2. 3. 2 Freundlich Adsorption non Isotherms

Freundlich model suggests energetically heterogeneous surface of porous matter so that adsorption capacity is due to adsorption temperature. Linear equation of Freundlich model is as follows:

$\ln q_e = \ln K + \frac{1}{n} \ln C_e$, where K is Freundlich constant related to maximal adsorption capacity, n is a constant related to adsorption density or binding strength $1/n$ is heterogeneity coefficient i.e. values of $1/n < 1$ refer to heterogeneous adsorbents while those values close or equal to 1 refer to relatively homogenous adsorbents at binding sites [23], $\ln K$, $1/n$ can be extrapolated from the slope of linear plot $\ln q_e$ with index of $\ln C_e$.

2. 4 Application test on industrial wastewater:

Wastewater samples were preconcentrated with APDC-MIBK extraction procedure according to the standard methods [24]. Total metal concentrations were measured by flame atomic absorption spectrophotometer (FAAS; Perkin Elmer A Analyst 100). Concentrations of heavy metals are expressed as (mgL^{-1}). Zeolite (chloropitilite), were applied to the same samples at the optimum conditions then simulated the removal rate of metals in wastewater. The same extracted method was applied to the wastewater after absorption with Zeolite.

3. RESULTS AND DISCUSSION

3. 1 Properties of Studied Zeolites

Zeolite sample is a non-dusting, hard and resistance to attrition, non-clouding in liquids (due to absence of clays), good permeability, relatively high density and high water retention. The qualitative composition of natural (clinoptilolite) zeolites, has obtained by X-ray spectroscopy analysis, where the physical properties and the results of chemical compositions present in zeolite along with peaks of all compounds as shown in Fig. 1, and presented in Table 1& 2. The natural (clinoptilolite) zeolites were composed mainly of SiO_2 and Al_2O_3 components whose Si/Al ratio becomes 1.88 that means there are two Si atoms for each single Al atom. While the MnO and K_2O contents were very low. The SNZ contained large amounts of CaO as compared with the other component, thus appears that a high CaO content might enable the formation of hydroxy sodalite. It has higher contents of calcium compound so it's called calcium zeolite.

3.1.1 Mineral component, %

The XRD patterns of zeolite and iron dust are shown in Fig.1. The XRD pattern of zeolite proved that the major part of it is Clinoptilolite. According to survey on the zeolite structure, absorption behavior in zeolite is based on Louise acid theory in pore structure [13]. The zeolite structure causes zeolite to have negatively charged surface. Negatively charged surface of zeolites can be used for adsorption of alkali earth metals. This structure consists of three dimensional frameworks of SiO_4 and AlO_4 that are linked to each other by sharing oxygen atoms. Thus, existing oxygen atom in tetrahedral structure of zeolite (Si-O-Al) lead to negative charge on adsorbent surface that are available sites for metal absorption. Therefore,

**TABLE 1. PHYSICAL PROPERTIES:**

Bulk (particle) Density, gmcm ⁻³	1.83
Overall Surface area, m ² gm ⁻¹	89.82
Porosity, %	27.80
Total pore area, m ² gm ⁻¹	35.836
Average pore diameter, μm	0.0181
Solubility, %	7.38
Swelling Index	2.52
pH	6.8
Apparent (Skeletal) Density, gmcm ⁻³	2.377
Appearance (Color)	Greyish-white
Humidity, %	6.75
Loss on ignition %	13.6
Hardness, Moh' no.	4
Grain Size	< 6 mm

Also, zeolite has cages and tunnels that can loosely hold water molecules in contrast to other tectosilicates such as feldspar and quartz. These channels and cages are adequate for adsorbing molecules smaller than these channels and/or tunnels, so in this regard, zeolites are known as “molecular sieves” [26].

Table 2. Chemical composition:

Cations, %		Major elements (oxides), %		Other elements, (trace)	
K ₂ O, %	3.266	SiO ₂	62.22	Cl	0.025
CaO, %	3.583	Al ₂ O ₃	11.096	BaO	0.085
Na ₂ O, %	0.780	Na ₂ O	0.78	P ₂ O ₅	0.033
		MgO	0.599	ZnO	0.025
		CaO	3.583	SrO	0.047
		Fe ₂ O ₃	4.033	PbO	0.002
		K ₂ O	3.266	MnO	0.120
		TiO ₂	0.339	SO ₃	0.035
		ZrO ₂	0.112		

The replacement of tetravalent silicon by trivalent aluminum in the mineral's structure creates a net negative charge that is counterbalanced by the presence of cations (usually Ca^{2+} , Na^{+} and K^{+}) which are situated in cavities [27, 28]. The removal of the heavy metal ions with zeolite is a result of ion exchange and/or adsorption property of zeolite. Both processes are parallel but one of them is prevailing depending on the solid to the liquid ratio, [29]. Ion exchange properties of zeolites are due to the weakly bonded extra-framework cations which are mobile and easily exchanged with solution

cations [30]. As it has been stated, removal of heavy metals from aqueous solution by means of zeolite mainly is based on adsorption and ion exchange process and a lot of researches have been done over the past decade. However, other mechanisms such as physisorption and chemisorption are also employed by zeolites for the sorption [31].

3. 2. Batch Adsorption Studies

3. 2. 1. Effect of adsorbent particle size

It's noticed from figure 2 that increasing the external surface area by reducing the adsorbent particle size, results in an increase in the number of available sites for metal uptake [32, 23]. Moreover, smaller particle sizes result in the shortening of the diffusion distance that heavy metals have to travel in order to get to an adsorption site, hence a faster rate of reaction. It's also noticed that Cd and Fe revealed the greatest affinity 80.9 and 79% while Ni revealed the lowest affinity (65.2 %). And the more metals were sorbed, however, by fine-grained zeolite than by coarse-grained zeolite [33].




Fig 2. Adsorbent particle size affecting on the removal of Cd, Fe, and Ni, from the solution ($C_0=2$ ppm · pH = 6 · m=0.5gr · V=50ml · T=180 min)

3. 2. 2. Effect of pH on adsorption

The solution pH is one of the crucial parameters in the sorption of heavy metals by zeolites, because of its effect on the charge state of metals and also adsorbent surface [34]. The effect of pH on studied metals uptake by zeolite was evaluated and shown in figure 3.




Fig. 3. pH affecting on the removal of Cd, Fe, and Ni, from the solution ($C_0=2$ ppm · size < 0.5 mm · m=0.5gr · V=50ml · T=180 min)

As is known, the cationic metals' adsorption efficiency is lower at acidic pH. It was observed that Cd, Fe, and Ni uptake increased with increase in pH up to pH of 6 and then it decreased with any further increase in pH. It is clear that at pH below 6, hydrogen ions compete with positive charge ions for adsorption sites. Therefore, this condition limits the access of metal ions to the adsorption sites and decreases metal removal [35]. Furthermore, at alkaline pH values, the adsorption of metals decrease because soluble hydroxylated complexes of the metal ions is formed and compete with metal for adsorption sites. Apart from affecting the characteristics of heavy metal ions and their sorption, pH can also affect the structure of zeolites. Aluminosilicate structure is vulnerable to strong basic and acidic environments. Strong bases can lead to desilication, whereas strong acids can break Al atoms. Zeolite structure can be destroyed at extreme pH values, which in turn can reduce sorption [36, 31]. Since zeolite is capable of changing the pH of the solution, there is a possibility for these processes to occur during the treatment of polluted water.

3. 2. 3. Effect of the initial heavy metal ion concentration

In the adsorption process, the initial concentration of ions in solution has a key role as a driving force to overcome the mass transfer resistance between the liquid phase and solid phase. Thus, it is expected that with an increase in metal ions the metal uptake will increase. [31]. The adsorption of Cd, Fe, and Ni as a function of their concentrations was studied at room temperature by varying the heavy metal ion concentration from 1 to 100 mg/L. The results are shown in Fig. 4.




Fig. 4. Initial heavy metal ion concentration (mg/l) affecting on the removal of Cd, Fe, and Ni, from the solution (size < 0.5 mm, m=0.5gr, V=50ml pH = 6, T=180 min)

The maximum amount of Fe, and Ni removal percentage for natural (clinoptilolite) zeolites at concentrations of 20 and 10 mg/l were obtained 68.7 % and 74.1 %, respectively. Instead, the removal percentage decreased from 80% to 42% for Cd for concentration 2 to 100 mg/l. The results also, showed that Fe, and Ni uptake rate were relatively high at the beginning of the process due to abundance available adsorption sites. However, the number of active sites for the adsorption gradually decreases with an increase in process time and the adsorption rate slightly decreased, leading to the formation of the adsorption equilibrium. At low metal concentrations, adsorption sites are available and could easily be occupied since the ratio between the number of metal moles in solution and available surface area is low. Therefore, adsorption is independent of the initial concentration. Nevertheless, at high concentrations of metal the removal efficiency is dependent on the initial concentration because the number of available sites is less than the number of metal moles. [37], stated when the initial concentration increases, the removal rate decreases. At higher concentration, the number of ions competing for the available binding sites on the biomass surface increases and thus reduces the number of binding sites. Meanwhile, at higher concentration, the average distance between the adsorbed species will be reduced, which affects the distribution of surface charge. Thus, the ability of adsorbate to migrate to the adsorbent surface changes and, as a result, the fixation reduces [38].

3. 2. 4. Effect of adsorbent dosage

Adsorbent dosage is one of the important parameters in adsorption processes because it determines the capacity of an adsorbent for a given initial concentration of the adsorbate under a given set of operating conditions [39]. To achieve this aim, a series of batch experiments were conducted with the adsorbent dose of 0.25, 0.5, 0.75, 1.0, 1.5, 2 and 4 g per 50 ml of test solution.




Fig. 5. Adsorbent dosage affecting on the removal of Cd, Fe, and Ni, from the solution (C₀= 2 ppm, size < 0.5 mm, pH= 6, V=50ml, T=180 min)

Figure 5 shows the effect of adsorbent dosage on the adsorption of Cd, Fe, and Ni ions. When the addition of the adsorbent dose increased, the percentage removal of metal ions also increased. A maximum removal of 80.1 %, 84.5 % and 77% of Cd, Fe, and Ni ions respectively was obtained at 1.0 g of the adsorbent. It can be seen from Figure 3 that an adsorbent dose of 1.0 g is sufficient for optimal removal of metal ions in aqueous solutions. A further increase in the quantity of adsorbent dose will not have any significant effect on the removal of metal ions from the solution. The initial increment in adsorption capacity with increase in adsorbent dosage was expected because as the adsorbent dose increases the number of adsorbent particles increases, thus more surface areas were available for metals attachment [40].

3. 2. 5. Effect of contact time

The effect of contact time on adsorption efficiency is depicted in Fig. 4. It is clear from Fig. 4 that the contact time needed to reach the maximum removal of metal by zeolite was dependent on the type of heavy metal [41].




Fig. 6. Contact time affecting on the removal of Cd, Fe, and Ni, from the solution ($C_0=2$ ppm, size < 0.5 mm, pH= 6, V=50ml, T=180 min)

The result of the effect of contact time on removal efficiency for Cd, Fe, and Ni, using 0.5 g zeolite at room temperature ($25\pm0.1^\circ\text{C}$) is represented in Figure 4. The adsorption rate was observed as rapid in the first 30 min, followed by a gradual increase with time until equilibrium adsorption was noticed at 90 min. The fast adsorption at the initial stage was probably due to the initial concentration gradient between the adsorbate in solution and the number of vacant sites available on the adsorbent surface. The attainment of equilibrium adsorption might have been due to reduction in the available active adsorption sites on the adsorbent with time resulting to limited mass transfer of the adsorbate molecules from the bulk liquid to the external surface of adsorbent [39].

3.3 Adsorption isotherms

Adsorption isotherms are an important factor in system design and describe the interaction between the adsorbent and adsorbate. Freundlich and Langmuir isotherm curves for the adsorption of Cd, Fe, and Ni ions from solution as shown in Tab 1 and Fig. s, reveal the reliability of experimental findings where the values of correlation coefficient R^2 range from 0.994-0.999, the maximal capacities of the given heavy metals adsorption q_0 according to Langmuir model are 10.08, 9.971, and 9.901 mg/g for Cd, Fe, and Ni respectively.

Table 3. Calculated equilibrium adsorption isotherm constants for the uptake of Cd, Fe, and Ni from solution by natural zeolite.

Heavy metals ions	Langmuir			Freundlich		
	q_0 (mg/g)	b	R^2	k	1/n	R^2
Cd	10.08	1.607	0.994	1.454	0.39	0.688
Fe	9.971	3.105	0.999	6.622	0.87	0.990
Ni	9.901	2.387	0.998	9.365	0.99	0.998

The maximal value is for Cd indicating to the higher selectivity of zeolite to Cd in comparison with other metals. Heterogeneity coefficient $1/n$ extrapolated from Freundlich isotherm curve is less than 1 and thus the evaluations are 0.39, 0.87, and 0.99 for Cd, Fe, and Ni respectively. The values indicate a material with relatively homogenous binding sites of natural porous Zeolite. It's been noticed from Fig. 7, the higher concentration of heavy metal ions the higher content of adsorbed metal per gram of natural Zeolite q_e this is attributed to the fact that at high concentration of heavy metal there is a higher solute concentration gradient; and this provides the necessary driving force for metal ions to displace exchangeable cations on the surface and from the internal micro-pores of natural zeolite [41]. The increase continues until the saturation point is achieved.




Fig. 7. Biosorption isotherms of nickel and chromium based on the Langmuir and Freundlich models

The removal efficiency (R%) of the metal ions on this adsorbent show good affinity of zeolite for a number of ions such as Cd, Fe, and Ni ions in water. The Langmuir and Freundlich models were investigated for adsorption isotherms that the Langmuir isotherm fitted with equilibrium data better than the Freundlich isotherm.

Application test on industrial wastewater:

The results presented in table 4, indicated a relatively high concentrations of measured heavy metals, since this sample is taken from mixed industrial wastewater and is characterized by high concentrations of these elements.

Table 4.The concentration of different heavy metals at industrial wastewater before and after application of zeolite.

Heavy metals mgL ⁻¹	Inlet			Outlet			Standard Limit Egypt
	Before	After	% removal	Before	After	% removal	
Cd	0.588	0.189	68.00	0.462	0.111	76.00	0.05
Fe	91.32	17.35	81.01	83.88	14.25	83.00	1.50
Mn	3.102	0.713	77.00	1.890	0.378	80.00	1.00
Ni	3.641	1.456	60.01	1.860	0.651	65.00	0.10
Pb	3.840	1.512	60.60	2.286	0.873	61.77	0.50
Zn	19.08	8.853	53.60	12.52	5.245	58.10	5.00

Industrial wastewater contains various metal ions with influence on potentiality of adsorbent to treat wastewater in competition for exchange sites and within adsorbent [23].




Fig. 8. Removal % of different heavy metals in both inlet and outlet samples from industrial wastewater after applying of zeolite.

From figure 8, it was observed that, the metal in industrial wastewater follow the order: Fe > Zn > Pb > Ni > Mn > Cd. These variations depend on the amount and the type of the effluent drained in the study area [43, 44]. These concentration values for metals in both inlet and outlet samples, exceed the maximum levels of the Standard limitations for discharge of industrial effluents in Egypt (Law 4/1994 for the disposal of the marine environment in Egypt).By applying zeolite the order became Fe> Mn > Cd > Ni > Pb > Zn. Each metal has a unique electronegativities, ionic size and bond strength which influence the adsorption capacity of the slag [45]. In treatment with zeolite, the removal of heavy metals from industrial wastewater sample is high whereby the percentage of removal is more than 50 percent of the initial concentration. The removal of heavy metals from industrial wastewater is effective using zeolite.

4. CONCLUSION

The removal of heavy metals from aqueous solution was carried out in batch adsorption mode using natural (clinoptilolite) zeolites adsorbent. The natural (clinoptilolite) zeolites exhibited effectiveness in the removal of Cd (II), Fe (III) and Ni (II) ions from aqueous solutions. There are many factors that affect the general reaction rate of adsorption process using natural zeolite. I.e. contact time, zeolite dose, particle size, effect of pH, and initial concentration of metal ions. It was found that the adsorption process is pH-dependent for studied metals, and the maximum uptake was obtained in the pH of 6.The optimal removal rate occurs after 2 hours of contact time, when using adsorbent particles of small size. The best isotherm fit for Cd, Fe, and Ni was obtained with Langmuir model. By applying to industrial wastewater, the result of the experiments determined that the natural (clinoptilolite)

zeolites could be used as an effective and low-cost method in removing metals from industrial wastewater. It is recommended to conduct a research on other toxic pollutant.

REFERENCES

1. Maleki A, Mahvi AH, Zazouli MA, Izanloo H, Barati AH. Aqueous Cadmium Removal by Adsorption on Barley Hull and Barley Hull Ash. *Asian J Chem*; 2011; 23(3): 1373-6.
2. Ibrahim WM, Mutawie HH. Bioremoval of heavy metals from industrial effluent by fixed-bed column of red macroalgae. *Toxicol Ind Health*; 2013; 29(1):38–42.
3. Hamedreza J, Ghorbani F, Tayebi H, Asl S. Study of the adsorption of Cd (II) from aqueous solution using zeolite-based geopolymer, synthesized from coal fly ash; kinetic, isotherm and thermodynamic studies. *Arabian Journal of Chemistry*, 2015; 8: 837–849. <http://dx.doi.org/10.1016/j.arabjc.2013.02.018>
4. Mohammadi T, Moheb A, Sadrzadeh M, Razmi A. Modeling of metal ion removal from wastewater by electrodialysis. *Separation and Purification Technology*, 2005; 41 (1): 73-82.
5. Matlock M, Howerton S B, Atwood A D. Chemical Precipitation of Heavy Metals from Acid Mine Drainage. *Water Research*, 2002; 36(19):4757-64. DOI: 10.1016/S0043-1354(02)00149-5.
6. Bakalár T, Milan B, Gajdošová L. Heavy Metal Removal Using Reverse Osmosis. *Acta Montanistica Slovaca. Ročník* , 2009; 14, číslo (3): 250-253.
7. Benítez P, Castro R, Barroso CG. Removal of iron, copper and manganese from white wines through ion exchange techniques: effects on their organoleptic characteristics and susceptibility to browning. *Analytica Chimica Acta*. 2002; 458: 197–202.
8. Ennigrou D J, Ali M. B, Dhahbi M, Ferid M. Removal of heavy metals from aqueous solution by polyacrylic acid enhanced ultrafiltration. *Desalination and Water Treatment*, 2015; 56 (10): 2682-268. <https://doi.org/10.1080/19443994.2014.982958>
9. Mohan D, Pittman, CU Jr. Activated carbons and low cost adsorbents for remediation of tri- and hexavalent chromium from water. *J Hazard Mater*, 2006; 137(2):762-811. DOI: 10.1016/j.jhazmat.2006.06.060
10. Mousavi, H Z, Seyedi S R. Nettle ash as a low cost adsorbent for the removal of nickel and cadmium from wastewater. *Int J Environ Sci Technol*; 2011; 8 (1):195–202.
11. Khachatryan Sh V. Heavy Metal Adsorption by Armenian Natural Zeolite from natural aqueous solutions. *Proc. of the Yerevan State Univ. Chemistry and Biology*, 2014; (2): 31–35.
12. Ahali Abadeh, Z, and Irannajad, M. Removal of Ni and Cd Ions from Aqueous Solution Using Iron Dust-zeolite Composite: Analysis by hermodynamic, Kinetic and Isotherm Studies *Chem. Res. Chin. Univ.*, 2017; 33(2), 318—326. doi: 10.1007/s40242-017-6150-x
13. Ibrahim M M, Sayyadi A S. Application of natural and modified Zeolites in removing heavy metal Cations from aqueous media: an overview of including parameters affecting the process. *International Journal of Geology, Agriculture and Environmental Sciences*, 2015; 3 (1-7).
14. Inglezakis V J, Loizidou, M M, Grigoropoulou HP. Ion exchange studies on natural and modified zeolites and the concept of exchange site accessibility. *Journal of Colloid and Interface Science*, 2004; 275(2):570-576. DOI: 10.1016/j.jcis.2004.02.070

- 407 15. Trgo M, Perić J. Interaction of the zeolitic tuff with Zn-containing simulated pollutant solutions.
408 Journal of Colloid and Interface Science. 2003; 260 (1): 166-175
- 409 16. Perić J, Trgo M.N, Medvidović V. Removal of zinc, copper and lead by natural zeolite -a
410 comparison of adsorption isotherms. Water Research, 2004; 38: 1893–1899.
- 411 17. Salunkhe B, Raut S J. Removal of Heavy Metal Ni (II) and Cr (VI) from aqueous solution by
412 scolecite natural zeolite. Int. J. Chem. Sci. 2012; 10 (2): 1133-1148.
- 413 18. Shaheen S M, Derbalah A S, Moghanm F S. Removal of Heavy Metals from Aqueous Solution by
414 Zeolite in Competitive Sorption System. International Journal of Environmental Science and
415 Development, 2012; 3 (4): 362- 367.
- 416 19. Visa M, Popa N. Adsorption of Heavy Metals Cations onto Zeolite Material from Aqueous Solution.
417 J. Membra Sci Technol, 2015; 5: 133. doi:10.4172/2155-9589.1000133
- 418 20. Hesnawi R, fateas J, Eswayah A, Maga R, Elshibany Y. Heavy Metal Removal from Aqueous
419 Solution Using Natural Libyan Zeolite and Activated Carbon. MAYFEB Journal of Environmental
420 Science, 2017; 1: 34-45.
- 421 21. Kremling K. Trace metals fronts in European shelf waters. Nature, 1983; 303: 225 - 227.
- 422 22. Gunay A, Arslankaya E, and Tosun I. Lead removal from aqueous solution by natural and
423 pretreated clinoptilolite: Adsorption equilibrium and kinetics. Journal of Hazardous Materials. 2007;
424 146:362-371.
- 425 23. Salman H, Shaheen H, Abbas Gh, Khalouf N. Use of Syrian natural zeolite for heavy metals
426 removal from industrial waste water: Factors and mechanism. Journal of Entomology and Zoology
427 Studies 2017; 5(4): 452-461.
- 428 24. APHA (American Public Health Association). Celesceri L-S, Greenberg A-E and Rhodes,R,
429 Trussell R-R (ed). B. Standard methods for the examination of water and waste water. Washington,
430 D.C., 17th edition, part 3, determination of metals, 1989: p 164.
- 431 25. Khashij M, Mousavi S A, Mehralian M, Massoudinejad M R. Removal of Fe²⁺ from Aqueous
432 Solution Using Manganese Oxide Coated Zeolite and Iron Oxide Coated Zeolite, International Journal
433 of Engineering (IJE), TRANSACTIONS B: Applications, 2016; 29 (11): 1587-1594. doi:
434 10.5829/idosi.ije.2016.29.11b.13
- 435 26. Mier M V, Callejas R L, Gehr R, Cisneros B E J, Alvarez P J J. Heavy metal removal with
436 Mexican clinoptilolite: multi-component ionic exchange. Water Research, 2001; 35: 373–378.
- 437 27. Dimirkou A, Doula M K. "Use of clinoptilolite and an fe-overexchanged clinoptilolite in Zn²⁺ and
438 Mn²⁺ removal from drinking water", Desalination, 2008; 224, (1–3): 280-292.
- 439 28. Motsi T, Rowson NA, Simmons M J H. "Adsorption of heavy metals from acid mine drainage by
440 natural zeolite", *Mineral Processing*, 2009; 92 (2): 42-48.
- 441 29. Cabrera C, Gabaldón C, Marzal P. Sorption characteristics of heavy metal ions by a natural
442 zeolite, J. Chem. Technol. Biotechnol., 2005; 80: 477–481.
- 443 30. Barkat M, Nibou D, Amokrane S, Chegrouche S, Mellah A. "Uranium (VI) adsorption on
444 synthesized 4A and P1 zeolites: Equilibrium, kinetic, and thermodynamic studies", *Comptes Rendus*
445 *Chimie*, 2015; 18 (3): 261-269.

31. Ziyath A M, Mahbub P, Goonetilleke A, Adebajo M O, Kokot S, Oloyede A. Influence of Physical and Chemical Parameters on the Treatment of Heavy Metals in Polluted Stormwater Using Zeolite—A Review. *Journal of Water Resource and Protection*, 2011; 3: 758-767 doi:10.4236/jwarp.2011.310086
32. Zorpas A A, Vassilis I, Loizidou M, Grigoropoulou H. Particle size effects on uptake of heavy metals from sewage sludge compost using natural zeolite clinoptilolite. *J. Colloid Interface Sci.*, 2002; 1(250): 1- 4.
33. Wingenfelder U, Hansen C, Furrer G, Schulin R. Removal of Heavy Metals from Mine Waters by Natural Zeolites *Environ. Sci. Technol.*, 2005; 39: 4606-4613.
34. Ebrahimi R, Zandi Sh, and Gharibi F. Removal of nickel and total chromium using *Escherichia coli* biofilm supported on clinoptilolite. *J Adv Environ Health Res*; 2014; 2(2): 126-33.
35. Lameiras S, Quintelas C, Tavares T. Biosorption of Cr (VI) using a bacterial biofilm supported on granular activated carbon and on zeolite. *Bioresour Technol*, 2008; 99(4): 801- 6.
36. Mishra T, Tiwari S K. “Studies on Sorption Properties of Zeolite Derived from Indian Fly Ash,” *Journal of Hazardous Materials*, 2006; 137 (1): 299-303. doi:10.1016/j.jhazmat.2006.02.004
37. Horsfall M, Ogban F, Akporhonor EE. Sorption of chromium (VI) from aqueous solution by cassava (*Manihot sculenta* Cranz.) waste biomass. *Chem Biodivers*, 2006; 3(2): 161-74.
38. Quintelas C, Fonseca B, Silva B, Figueiredo H, Tavares T. Treatment of chromium(VI) solutions in a pilot-scale bioreactor through a biofilm of *Arthrobacter viscosus* supported on GAC. *Bioresour Technol*; 2009; 100(1): 220-6.
39. Mehdizadeh S, Sadjadi S, Ahmadi S J, Outokesh M. Removal of heavy metals from aqueous solution using platinum nanoparticles/Zeolite-4A. *Journal of Environmental Health Science & Engineering* 2014; 12:7.
40. Acharya J, Sahu, J N, Mohanty, C R, Meikap B C. Removal of lead (II) from wastewater by activated carbon developed from Tamarind wood by zinc chloride activation. *J Chem Eng* 2009; (149):249–262.
41. Taamneh Y, Sharadqah S. The removal of heavy metals from aqueous solution using natural Jordanian zeolite. *Appl Water Sci* , 2017; 7:2021–2028. DOI 10.1007/s13201-016-0382-7
42. Abadzic S D, Ryan, J N. Particle release and permeability reduction in a natural zeolite (clinoptilolite) and sand porous medium. *Environmental Science and Technology*, 2001; (35):4501-4508.
43. Abd El-Azim, H. Heavy metals in Suez Canal relevant to land based sources. Ph. D. Thesis, 2002; Fac. Sci., Mansoura Univ., Egypt.
44. Halimoon N, Yin R G. Removal of Heavy Metals from Textile Wastewater using Zeolite. *EnvironmentAsia*, 2010; 3(special issue): 124-130.
45. Gomes P C, Fontes M P F, da Silva A G, de S, Mendonça E, Netto A R. Selectivity sequence and competitive adsorption of heavy metals by Brazilian soils. *Soil Sci. Soc. Am. J.*, 200; 65:1115–1121.