

Title

“Generation and analysis of biogas from some animal and vegetable wastes.

Abstract

The world relies heavily on fossil fuels for both domestic and commercial energy needs but there is the environmental effects of these fossil fuels and as the energy consumption is becoming very high there is depletion of the fossil fuels. Research has to be in the development of alternative energy sources. One of the alternative sources of energy is bio-energy. The common fuels obtainable from biomass are bio-ethanol and biogas. This study aims at the production of biogas from biologically degradable wastes by co-digestion system and analyzing the percentage composition of CH₄ and CO₂ in biogas produced. It involves using fruit (peels and seeds of orange, tomato, cucumber) and vegetable (efo shoko-leafy vegetable) wastes mixed with pig manure in an anaerobic digester. thus giving an alternative energy source and making the environment cleaner by reducing the green energy gases and wastes. The methane content has to be high to support a viable work. The gas content therefore is analysed. The composition of CO₂ and CH₄ content in biogas generated were CO₂ 28.1% and CH₄ 68.9%

Phytochemical screening, proximate analysis of the fruit waste, vegetable waste and the pig waste were carried out. The phytochemical studies were carried out according to the protocols of Evans. The proximate analyses was carried out for carbohydrates using Anthrone method, Total Lipids Using Bligh & Dyer Method; Crude Fibre, moisture content, total ash, and crude protein method as described by AOAC (1995); The moisture content of the agricultural wastes and the pig manure ranged from 61% to 87.35% this will help to increase methanogenic activity at pH 6.41 used. The high content of the methane obtained is a high indication that the waste materials used are a good source of biogas generation and can be used to provide a cleaner environment.

Key words: Biogas, waste products, methane, biomass

Introduction

There are various sources of energy, but the ones mostly used are from fossil fuels. The by products of fossil fuels are harmful to the environment because of pollution. Alternative sources of energy are needed now and this is found in bioenergy. Biogas can be generated when organic matter is fermented with the assistance of micro organisms in the absence of air or oxygen (Heb,

2009). The production of biogas plays an important role in reducing greenhouse gases emissions and facilitate a sustainable development of energy supply. The process of production only use energy from renewable energy sources. Hence, no net carbon dioxide is added to the atmosphere, making it environmentally benign energy source.

Biogas is a combustible mixture of gases consisting mainly of methane (CH_4) and carbon dioxide (CO_2). The gases formed are the waste products of the respiration of the decomposer microorganisms and the composition of the gases depends on the biomass and the various compositions that are being decomposed. If the material consists of mainly carbohydrates, such as glucose and other simple sugars and high-molecular compounds (polymers) such as cellulose and hemicellulose, the methane production is low. However, if the fat content is high, the methane production is likewise going to be high (Jørgensen, 2009). The generation of biogas is a form of renewable energy, because it is generated from organic wastes by anaerobic fermentation. Anaerobic digestion of agricultural wastes is of increasing interest in order to reduce the greenhouse gas emissions and production of biogas provides a versatile carrier of renewable energy, as methane can be used for replacement of fossil fuels in both heat and power generation and as a vehicle fuel. The residue from anaerobic fermentation is a valuable fertilizer due to the increased availability of nitrogen. Anaerobic treatment minimizes the survival of pathogens which is important for using the digested residue as fertilizer.

Biogas-generating technology is a favorable dual-purpose technology at present: the biogas generated can be used to meet energy requirements while the organic residue is a useful fertilizer. This in turn will give a cleaner environment. The production of methane during the anaerobic digestion of biologically degradable organic matter depends on the amount and kind of the material added to the system. In India and China alone, there are more than one million small, simple plants, each treating waste (sewage, animal manure, crop residues, etc.) from a single household. The biogas is used in the housekeeping for cooking and the digested biomass used as a fertilizer.

Materials and Methods

Substrate collection

Fruit and vegetable wastes were collected from an Ikorodu market and mixed with pig manure collected from a pig farm in Ogun state is used as substrates for biogas production.

Fabrication of Anaerobic Digester

The anaerobic biogas generation digester of fruit and vegetable wastes mixed with pig manure was fabricated using two (20L) plastic container, two $\frac{1}{2}$ inch plastic valve, glue, bicycle tube and gas hose $\frac{1}{2}$ inch diameter $\times$ 40cm length. An opening was made on the cover of the two plastic containers just about the size of the plastic valve, the valves were inserted into opening made on the cover while glue and clay was added around the sides of the valve to make it air tight and firm. Then, gas hose $\frac{1}{2}$ inch diameter $\times$ 40cm were firmly inserted into the valves and channeled into a bicycle tube which will serve as storage for the gas generated.

Sample Preparation.

The mixture of biodegradable waste - peels and seeds of orange, tomato, cucumber, efo shokor (leafy vegetable) were chopped into smaller size, slurry obtained by mixing fresh pig manure and tap water. The mixture of the waste was : pig manure 3kg, the others 0.5kg each so the ratio was 3:2 in the first digester. The mixture of the waste in the second digester was : pig manure 10kg, the others 2kg each so the ratio was 5:4.

5kg of the substrate was fed into the first digester while 17kg of substrate was fed to the second digester before the mouth was properly sealed. The two digesters were fed once and placed in an open space. The temperature was between 25 and 30°C at atmospheric pressure for twenty two days.



Figure 1: The fabricated digester

Data Collection and Analysis

Proximate analysis (carbohydrates, crude fibre, moisture content, crude ash, protein and crude fat) was carried out on wastes materials used.

The CO₂ and CH₄ composition of biogas was also determined using absorption method.

Ca(OH)₂ was prepared to absorb CO₂ from biogas (purifying the gas) while the percentage of CO₂ absorbed is calculated using

$$\% \text{ of CO}_2 = \frac{M_1 - M_2}{M_1} \times 100. \quad 1M \text{ NH}_3 = M_1V_1 = M_2V_2$$

Where M₁ = mass of biogas before removal of CO₂

M₂ = mass of methane and other gases after removal of CO₂

$$\% \text{ of CH}_4 = 100\% - (\text{CO}_2 + 3\% (\text{H}_2\text{S} \text{ and other gases}))$$

The 3% average is given to (H₂S and other gases) because they range between 1-5% in biogas composition.

To validate, the amount of CO₂ in CaCO₃ formed is determined by Standardization of EDTA with CaCO₃

Reagents used and Preparation

- i. EDTA
- ii. ZnSO_4 to standardize EDTA
- iii. Ammonia buffer solution
- iv. Eriochrome black T indicator.
- v. $\text{Ca}(\text{OH})_2$

Table 1: Proximate Analysis of The Vegetables, the Fruits and the Pig Dung

Parameters	CHO %	Protein %	Crude Fat %	MOISTURE %	ASH %	Crude Fibre%
Leafy Vegetable	8.89	1.20	0.195	65.5	4.50	3.62
Cucumber	4.77	2.02	0.08	72.28	3.32	0.54
Orange	7.45	1.11	0.16	80.7	1.08	1.90
Tomato	15.17	7.00	6.17	61.0	2.30	8.91
Pig Dung with pH 6.41		1.60	0.14	87.35	2.60	0.04

Results and Discussion

Effect of moisture:

The moisture content of the materials used range from 61% to 87.35%. Pig manure had the highest moisture content, the moisture content are high for the agricultural wastes used. This will help the relative methanogenic activity to increase and the rate of methane production will function with optimum at pH 6.41. High moisture content provides greater activity of water as

soluble enzymes and coenzymes needed for metabolic activities will help the growth of microorganisms. (Iheanacho and Udebuani, 2009).

Effect of minerals:

The ash content values which range from 1.08% to 4.50% confirms presence of essential minerals like calcium, sodium, potassium but when in high quantity could be used to retard growth of certain microorganisms due to presence of toxic elements. These values are not too high.

Effect of crude fiber:

The values for crude fiber ranged from 0.04% - 8.91%, these values are fairly low. Lee *et al.*, 2003 in their paper stated that crude fiber is an important component of methane production. He also stated that methane production decreases as the content of crude fiber increases, this confirms that substrate with the lowest crude fiber have the highest methane production. The low content is an advantage to the waste materials content used in this research.

Effect of crude fat:

The crude fat ranged from 0.08% to 6.17% the proportion of carbohydrate, protein, and lipid in a feedstock will influence biogas yield and composition with lipid yielding higher volumes of biogas per gram of feed material than both carbohydrate and protein (Weiland 2010, Heaven *et al.*, 2011,).

Effect of Carbohydrate:

The carbohydrate content ranged from 4.77% - 15.17% which is fairly low. However, if material that is been decomposed consists mainly of carbohydrate methane production will be low due to the fact that microbes involved in digesting carbohydrate rich diet are different, they would produce propionate which will remove hydrogen from methane production.

Effect of Crude protein:

The crude protein values ranged from 1.11% to 7.00%, this is fairly low. Crude protein measures all sources of nitrogen in feedstock, high protein feedstock could modulate bacteria fermentation in the digester.

The presence of these and in the various compositions is able to help in the methane content.

Biogas Production

Biogas generation in one of the digesters constructed was evident as pressure build-up was noted after 14 days of startup

Shown in **Fig 2** below



Biogas Composition:

Percentage of methane and carbon dioxide in biogas varies with the maturities of feed stock, temperature, water content, loading rate of raw material and bacterial actions.

Table 2: The Percentage composition of the CH₄ and CO₂

Biogas Composition	CH ₄	CO ₂
	68.9 %	28.1 %

Conclusion

This investigation shows that biogas can be successfully produced from co-digestion of manure with fruits and vegetable wastes without any chemical addition to the system. The quality of

methane composition in biogas and quantity of biogas produced depends on the composition of materials fed to the digester, fat and moisture content is important in methane yield. Through anaerobic digestion of fruit and vegetable wastes we can avoid the emission of harmful greenhouse gases and make a positive contribution to a cleaner environment. Production of biogas from fruit and vegetable waste and pig dung is a major step toward harnessing the least utilized renewable energy resource. From this work, methane gas has been produced. The CO₂ generated in the mixture can be removed. The methane content is high, no additional energy was used as the microorganisms were used in anerobic condition, in the generation of the biogas.

References

1. Peter Jacob Jørgensen, (2009). Biogas Green energy: Process, Design, Energy Supply, and Environment: p 8-15
2. Heb, F. Decentralised Anaerobic Digestion of Market Waste – A Case Study inThiruvananthapuram, India. Sandec Report. 2009.
3. Fandi Suprianto D., Willyanto Anggono., Michael S C Tanoto., (2016). Effect of Carbon Dioxide on Flame Characteristics in Biogas External Premix Combustion. International Journal of Applied Engineering Research ISSN 0973-4562 Volume 11, Number 4 pp 2240-2243.
4. Garba,B. and Sambo, A.S. (1995). Effect of Some Operating Parameters on Biogas Production rate. Nigerian Journal of Renewable Energy, 3:36-44.
5. Gregor Zupančič D., and Viktor Grilc., (2012). Anaerobic Treatment and Biogas Production from Organic Waste: p 4-13.
6. Sagagi, B. S., Garba B., N. S. Usman., (2009). Studies on Biogas Production from Fruit and Vegetable wastes. Bayero Journal of Pure and Applied Sciences, 2(1): 115 – 118.
7. [Weiland P](#) (2010) Biogas production: current state and perspectives. [Appl Microbiol Biotechnol](#). 85(4):849-60. doi: 10.1007/s00253-009-2246-7.

182 8. Iheanacho, Kizito M.E, Udebuani, Angela C. **2009** Nutritional Composition of Some Leafy
183 Vegetables Consumed in Imo State, Nigeria J. Appl. Sci. Environ. Manage. Vol. 13(3) 35
184 - 38

185
186

187