

Original Research Article**Evaluation of *Momordica Balsamina* Seed Oil for its Potential as Feedstock
for Biodiesel Production****Abstract**

This paper sought to evaluate the potential of oil obtained from balsam apple (*M. balsamina*) for biodiesel production. Oil was extracted from the seed using n-hexane in a soxhlet extractor, then transesterified to biodiesel using single step alkali hydrolysis. The biodiesel so produced was analyzed for their physicochemical and fuel properties using American Standards for Testing and Materials procedures. GC-MS was used to quantify the Fatty acid methyl esters yield. Percentage oil yield was 33.21 ± 0.18 %. The physicochemical properties of the oil showed high acid values (*M. balsamina* 9.958 ± 0.5 mg/KOH/g). The percentage oil degumming was 10.12 ± 0.6 %. Some critical fuel parameters for the biodiesel produced from the oil showed compliance with American Standards for Testing and Materials and European standard specifications. The result of biodiesel produced showed; Colour 2.9 ± 0.0 , cetane number 57.699 ± 0.23 , flash point 137 ± 0.00 °C, cloud point 1.0 ± 0.00 °C, pour point -0.4 ± 0.0 °C, sulphur content 0.021 ± 0.01 ppm, kinematic viscosity 3.82 ± 0.0 mm²/s and specific gravity 0.8615 ± 0.0 g/cm³. The percentage yield of biodiesel was 89.12 ± 0.04 %. Stearic acid methyl ester, a saturated ester, was dominant with percentage of 14.03 % in the biodiesel produced. The yield of the oil is high enough and comparable with other oils that have been used for biodiesel production. It can be inferred that oil from *M. balsamina* is suitable for biodiesel production.

Keywords: *M. balsamina*, transesterification, biodiesel, cetane number.

1.0 Introduction

There is a need for alternative energy sources to petroleum based fuels due to the depletion of the world's petroleum reserves, global warming and environmental concern which makes it necessary to develop renewable energy sources of limitless duration and smaller environmental impact than the traditional one. One possible alternative to fossil fuel is the use of oils of plant origin like vegetable oils and tree borne oil seeds. These oils, after being formulated, have been found suitable for utilization in diesel engines [1].

Recently, environmentalists have started to debate on the negative impact of biodiesel production from edible oil due to large-scale production of biodiesel from edible oils which may bring global in balance to the food supply and market demand [2]. Hence, in this paper non edible vegetable oil from *Momordica balsamina* seed oil was assessed as potential alternative fuel for economic development and to solve environment issues.

2.0 Materials and Methods

2.1 Sample collection and preparation

Sample was collected from ripped seeds of balsam apple; *M. balsamina* in Kawo Area within Kaduna metropolis. The leaves and seeds were identified in the Herbarium section of Biological Science Department, Ahmadu Bello University Zaria with a Voucher numbers 1139 and was kept for future reference. The seeds were peeled to obtain the kernels, which was air dried and pulverized to a fine powdered form and stored in an air tight plastic containers.

2.2 Extraction procedure

Two hundred gram (200 g) of air dried and pulverized plant seeds of *M. balsamina* was weighed out and packed into a thimble, which were in turn placed into soxhlet extractor. Extracting solvent n-hexane (500 cm³) and anti - bumping chips were put into a 1000 cm³ round bottomed flask and heated on heating mantle at 60 °C. The extraction was allowed to continue until the solvent was cleared. The solvent in the round bottomed flask were collected and concentrated in vacuo using a rotatory evaporator at 40 °C. The process was repeated to obtain the mean of the percentage extraction and enough oil for further analysis.

$$\% \text{ Extraction} = \frac{\text{Weight of oil extracted}}{\text{Weight of sample}} \times 100$$

2.3 Pre-treatment of the Oil (Acid Degumming)

Two hundred (200 gram) of *Cucurbita maxima* oil was weighed and heated to 70 °C on a heating mantle. 25 % citric acid was prepared by dissolving 250 g citric acid in 1000 cm³ of distil water and was added in the ratio of 3:1 citric acid to oil then mixed for 5 min. This was centrifuge for 30 min for separation of gums and other impurities which settled at the bottom. Oil at the top of the centrifuge test tubes, was decanted and reheated [3]

2.4 Physicochemical Properties of the Seed Oil

2.4.1 Determination of the saponification value

The American Standard for Testing and Material (ASTM) method- (D 5558-95) was used for the determination of the saponification values of the vegetable oil. The oil (5 g) was weighed into Erlenmeyer flask and 0.5 M ethanolic KOH was prepared by dissolving 7 g of KOH in 250 cm³ ethanol and 25 cm³ of the prepared 0.5M ethanolic KOH was added and the resulting mixture

was refluxed for 60 minutes. The resulting solution was subsequently titrated against 0.5 M HCl prepared by diluting 10.7 cm³ HCl in 250 cm³ of distil water using phenolphthalein as indicator. The resulting end point was obtained when the pink colour changed into colourless. The same procedure was used for the blank. The Saponification value (SV) was then calculated using the expression;

$$\text{Saponification value (S.V.)} = \frac{5.61 (B-S) \times M \text{ of HCl}}{\text{Weight of sample}}$$

(Source: ASTM-D 5558 (95))

Where;

B – Vol. of HCl required by blank

S – Vol. of HCl required by sample

M – Molarity of HCl

5.61– Molar mass of KOH

2.4.2 Determination of acid value

Acid value of the oil was determined by ASTM method (ASTM – D 974(00)). The oil (0.5 g) of the oil was weighed into 250 cm³ conical flask and 50ml of neutralized ethyl alcohol was added, prepared by neutralizing a solvent mixture of 25 cm³ ethanol and 25 cm³ diethyl ether with 0.1M ethanolic KOH prepared by dissolving 1.4 g KOH in 250 cm³ of ethanol using phenolphthalein as indicator. The mixture was added to the oil and heated on a water bath to dissolve the oil. The solution was then titrated against 0.1 M KOH prepared by dissolving 1.4 g of KOH in 250 cm³ of distill water using phenolphthalein as indicator. The acid value was determined after which the free fatty acid was calculated respectively as follows;

$$\text{Acid Value} = \frac{A \times M \times 56.10}{W}$$

$$\text{W}$$

(Source: ASTM-D 974 (00))

Where,

A = ml of 0.1M KOH consumed by sample

M = Molarity of KOH

W = weight in grams of the sample

Then,

$$\text{Free fatty acid} = \frac{\text{Acid Value}}{2}$$

$$2$$

2.4.3 Determination of iodine value

The oil (0.5 g) was weighed into conical flask and 20 cm³ of carbon tetrachloride was added to dissolve the oil. 25 cm³ of Wijs reagent was added into the flask using a measuring cylinder in a fume chamber and a stopper was inserted, the content of the flask was vigorously swirled and kept in the dark for 35 minutes. 20 cm³ of 10 % aqueous potassium iodide prepared by diluting 10 cm³ of potassium iodide in 90 cm³ of distill water was added into the content of the flask using a measuring cylinder. The content was titrated with 0.1M sodium thiosulphate solution prepared by dissolving 3.95 g of anhydrous Na₂S₂O₃ in 250 cm³ of distill water. Few drops of 1 % starch indicator were added and the titration continued by adding the sodium thiosulphate drop wise until coloration disappeared after vigorously shaking. The same procedure was used for the blank test. The Iodine Value (I.V) is given by the expression;

$$\text{Iodine Value (I.V)} = \frac{126.9C(V_1 - V_2)}{M}$$

$$M$$

124 Where,

125 C = concentration of sodium thiosulphate

126 V_1 = volume of sodium thiosulphate used for blank

127 V_2 = volume of sodium thiosulphate used

128 M = mass of sample

129 12.69= Constant.

130

131 **2.4.4 Determination of refractive index**

132 Abbey refractometer was used in this determination. A drop of the sample was transferred into a
 133 glass slide of the refractometer. Water at 30 °C was circulated round the glass slide to keep its
 134 temperature uniform. Through the eye piece of the refractometer, the dark portion viewed was
 135 adjusted to be in line with the intersection of the cross. At no parallax error, the pointer on the
 136 scale pointed to the refractive index. This was repeated and the mean value noted and recorded
 137 as the refractive index.

138

139 **2.7.0 Determination of Fuel Properties of Biodiesel**

140 **2.7.1 Determination of pour point**

141 The pour point was determined by ASTM method (ASTM D – 97). The oil sample was poured
 142 into the test jar to the level mark. The test jar was closed with the cork carrying the high – pour
 143 thermometer. The position of the cork and the thermometer were adjusted for the cork to fit
 144 tightly, the thermometer and the jar were coaxial and the thermometer bulb was immersed 3mm
 145 below the surface of the sample. After this, the test jar was placed into the cooling medium. The
 146 sample was cooled at a specified rate and examined at interval of 3 °C for flow characteristics

until a point was reached at which the sample showed no movement when the test jar was held in a horizontal position for 5 seconds. The observed reading of the thermometer was recorded. 3 °C was added to the recorded temperature and the result was recorded as the pour point

2.7.1 Determination of kinematic viscosity

The temperature of the viscometer bath was adjusted to 38.9 °C. A calibrated thermometer was held in upright position and inserted into the bath by a holder. A clean dry calibrated viscometer was selected and carefully flushed with a dry nitrogen gas to remove the moist room air. A sample of the biodiesel was drawn up into the working capillary of the viscometer and the timing bulb was then allowed to drain back as an additional safeguard against moisture condensing or freezing on the walls. The charged viscometer was inserted into the bath at a depth such that at no time during the measurement of the flow time was any portion of the sample in the viscometer less than 20 mm below the surface of the bath. The viscometer together with its content was allowed to remain in the bath for 30minutes to reach the test temperature (38.9 °C). A suction bulb was used to adjust the head level of the biodiesel to a position in the capillary arm of the viscometer about 7 mm above the first timing mark. The biodiesel was then allowed to freely flow and the time required for the meniscus to pass from the first to the second timing marks was noted with a stop watch. The procedure was repeated to make a second measurement of flow time and the average of these determinations was used to calculate the kinematic viscosity. The viscometer was thoroughly cleaned with sample solvent and dried by vacuum. The procedure was repeated for the other samples of the biodiesel (ASTM D 445-97)

Calculation:

$$v = C \times t$$

Where,

v = kinematic viscosity, mm²/s

C = calibration constant of the viscosity, (mm²/s)/s

t = mean flow time

2.7.3 Determination of Cloud point

The cloud point was determined using ASTM D2500. A cylindrical test tube was filled with the biodiesel to a specific level (5 cm³) and clamped with a wooden clamp bearing thermometer. The test tube was placed on the ice/salt bath and the set up inspected at intervals for cloud formation. The temperature at which a distinct cloudiness appeared at the bottom of the test tube was observed and recorded as the cloud point of the biodiesel.

2.7.4 Determination of Flash point

The flash point was determined using ASTM D93. Seta Multiflash Pensky-Martens Flash Point Module Part Number 34100-2 was used to determine the flash point. The automatic PMCC module conforms precisely to national and international Pensky-Martens Closed Cup flash point test methods. It comprises a heated cup and lid, and a DIPS pod containing the dipping mechanism, gas and electric ignitors, fire detection system and a stirrer. The Pensky- Martens module was used with the Multiflash Universal Base unit (p/n 34000-0). The base unit recognises the Pensky-Martens module is connected and instantaneously sets up standard test parameters and calibration data

193 **2.7.5 Determination of Cetane number**

194 The cetane number was determined based on the formula proposed by Demirbas 2009 as
195 there was no enough biodiesel to carry out the test. The formula is given below.

$$\begin{aligned} 196 \quad \text{CN} &= \frac{46.3 + 5458}{\text{S.V} - 0.225 \times \text{I.V}} \\ 197 \quad & \\ 198 \end{aligned}$$

199 Where,

200 S.V = Saponification of the biodiesel

201 I.V = Iodine Value of biodiesel

202

203 **2.7.6 Determination of Specific gravity**

204 Specific gravity bottle was washed, rinsed with acetone and dried at room temperature in
205 a dessicator and the weight of the empty bottle determined using an electronic weighing
206 balance. The weight of the bottle filled with water was recorded. The same procedure was
207 repeated with the oil and the specific gravity computed as follows;

$$\begin{aligned} 208 \quad \text{Specific gravity} &= \frac{\text{W2} - \text{W1}}{\text{W3} - \text{W1}} \\ 209 \end{aligned}$$

210 Where,

211 W1 = weight of empty bottle

212 W2 = weight of bottle + oil

213 W3 = weight of bottle + water

214

215

216

3.0 RESULTS

Table 1: Physicochemical properties of the seed oils

Oil property	Unit	<i>M. balsamina</i> (Balsam Apple)
Oil Content	%	$33.21 \pm 0.18\%$
Saponification Value	mgKOH/g	207.57 ± 0.02
Iodine Value	gI ₂ /100g	171.31 ± 0.59
Peroxide value	Meq/kg	1 ± 0.2
Acid value	mgKOH/g	9.958 ± 0.5
Relative density	Dimensionless	0.874 ± 0.0
Refractive index	Dimensionless	1.481 ± 0.0
Free fatty acid	Percentage	4.979 ± 0.6
Unsaponifiable value	mgKOH/g	2.98 ± 0.0
Gums	%	$10.12 \pm 0.6\%$

223 **Table 2: Result of GC-MS for Biodiesel Produced from Balsam Apple (BOME)**

224

FATTY ACID	CARBON NUMBER	MOLECULAR FORMULAR	% COMPOSITION
Azelaic Acid	C10:2	C ₁₁ H ₂₀ O ₂	0.72
Linoleic Acid	C18:2	C ₁₉ H ₃₄ O ₂	11.48
Palmitic Acid	C16:0	C ₁₇ H ₃₄ O ₂	7.94
Stearic Acid	C18:0	C ₁₉ H ₃₈ O ₂	14.03
Alaidic Acid	C18:1	C ₁₉ H ₃₆ O ₂	8.43
Cerotic Acid	C26:1	C ₂₇ H ₅₄ O ₂	10.18
Behenic Acid	C22:0	C ₂₃ H ₄₆ O ₂	10.18
Eicosanoic Acid	C20:1	C ₂₁ H ₄₂ O ₂	4.68
Eicosatrienoic Acid	C20:2	C ₂₁ H ₅₄ O ₂	8.09
Linolenic Acid	C18:2	C ₁₉ H ₃₂ O ₂	9.67
Non-methyl esters	-----	-----	14.6
Total	-----	-----	

225

226 **Table 3: Fuel Properties of Biodiesel Produced from Balsam Apple (Mean \pm SD)**
227

Fuel parameter	BOMEs	ASTM Limits	European Standard
(%)Yield of Biodiesel	89.12 \pm 0.06	-	-
Colour	2.9 \pm 0.0	3.5	-
Specific gravity g/cm ³	0.8615 \pm 0.0	-	-
Kinematic viscosity (mm ² /s)	3.82 \pm 0.0	6.0 Max	3.5-5.0
Pour point (°C)	-0.4 \pm 0.0	NS	NS
Cloud Point (°C)	1.0 \pm 0.0	NS	NS
Flash point (°C)	137 \pm 0.0	130 min	<120
Sulphur content (ppm)	0.021 \pm 0.01	0.050	-
Cetane number	57.699 \pm 0.23	Min47	-

228
229 NS = Not specified BOME = Balsam Oil Methyl Ester
230

231

232

4.0 Discussions

The results of the physical and chemical properties of *Momordica balsamina* oil seed studied is presented in Table 1. The percentage oil content of *Momordica balsamina* is 33.21 ± 0.18 %. According to Food and Agricultural Organization (FAO) as reported by [4], any seed containing greater than 17 % of oil is considered to be an oil seed and can be utilised as feedstock for biodiesel production, as such *Momordica balsamina* seeds are good feedstock for biodiesel.

The relative density of the *Momordica balsamina* oil was found to be 0.874 ± 0.0 , which is higher than the relative density of Africa star apple seed oil 0.711 [5] and Horse eye seed oil 0.847 [6]. The higher relative density observed in the *Momordica balsamina* seed oil when compared with other literatures is due to the fatty acid composition, minor components and temperature. Since the relative density of seed/vegetable oils are dependent on this factors as reported by [7]. This in turn will affect the viscosity of the *Momordica balsamina* seed oil resulting in poor atomization of the biodiesel produced from the seed oil in the engine performance.

The refractive index of the oil is 1.473 ± 0.0 . This value is lower than that of beniseed oil (1.474) [8]. The refractive index of an oil is the ratio of speed of light at a defined wavelength to its speed in the oil/fat itself [9]. The difference in the refractive index of the *M. balsamina* oil compared with similar seed oils reported in literature is due to the variation in wavelength and temperature, degree of unsaturation and substitutions of component fatty acids.

The acid value of *Momordica balsamina* was found to be 9.958 ± 0.5 mgKOH/g. The acid value of oil was higher in comparison to the acid value of Egusi seed oil (4.0 mgKOH/g) [10] and rubber seed oil (8.17 mgKOH/g) [11]. These indicate that the oil will be unstable over a long period of time and will not be protected against rancidity and peroxidation. This could be attributed to lack of natural antioxidants in the seeds such as vitamins C and A as well as other possible phytochemicals like flavonoids [9]. The lower the acid value, the lower the free fatty acid, the more suitable, the oil for transesterification process.

The saponification value for was found to be 210.38 ± 0.02 mgKOH/g, which is lower when compared with *cocos nucifera* or coconut oil 246 mgKOH/g [11]. However biodiesel derived from oil with high saponification value causes exhaust emissions during burning in the engine [12].

The iodine value was found to be 182.74 ± 0.4 gI₂/100g, which is higher than the iodine value of refined 87.72 gI₂/100g and unrefined castor oil 84.8 gI₂/100g [8]. This indicates that the oil studied is suitable for biodiesel production since low iodine value of vegetable oil produces biodiesel with high cloud and pour points; higher cloud and pour points means poor engine performance in cold temperatures [10].

The viscosity for the oil was found to be 25.0 ± 0.0 mm²/sec, which is lower compared to the viscosity of *Cucurbita pepo* oil 93.65 mm²/sec [13] and *black benised* seed oil 33.2

mm²/sec [14]. According to [15] viscosity increases with molecular weight, as such *Momordica balsamina* is having high molecular weight, which in turn will affect injection lubrication, increase engine deposits and fuel atomization [16]

The peroxide value of *Momordica balsamina* was 1 ± 0.2 Meq/kg and is considered lower compared with Melon seed oil 5.63 Meq/kg [17] but higher than groundnut seed oil 0.74 Meq/kg that have been used in biodiesel productions [18]. The peroxide value of *Momordica balsamina* indicates that *Momordica balsamina* will have less level of deterioration when attacked or exposed to oxygen, since peroxide value indicates the level at which deterioration will take place as a result of oxidation owing to the availability of oxygen during storage [19].

The unsaponifiable value for *Momordica balsamina* was found to be 3.20 ± 0.4 mgKOH/g, which is higher compared to African pear seed oil 2.62 mgKOH/g and Soy bean seed oil 0.837 mgKOH/g [20]. The high level of the unsaponifiable matter in the oils indicates the presence of good lubricating properties [21].

The percentage degumming after centrifugation of *Momordica balsamina* was 10.12 ± 0.6 %. This is above the percentage degumming of crude Canola oil 4.50 ± 0.0 % and crude Sunflower oil 3.20 ± 0.0 % [3]. The value indicates that there is high level removal of hydratable and non-hydratable phosphatides, and other impurities especially metals contamination (P and Ca specifically) and also improvement in the yield of biodiesel production [22].

4.3 Fatty acid methyl esters

The result of fatty acids methyl esters in Balsam Oil Methyl Esters (BOMEs) biodiesel shown in Table 2 indicate that stearic acid methyl esters been the dominant ester will help in enhancing the stability of the biodiesel, it is a saturated compound and less susceptibility to peroxidation [23]. It is also observed that balsam oil methyl ester is having more long chain of acid methyl esters, as such the long chain of balsam oil methyl ester will have effect on the fuel properties of the biodiesel produced [24].

4.4 Fuel properties

The fuel properties of Balsam Oil Methyl Esters (BOMEs) produced is shown in Table 3. The percentage yield was recorded to be $89.12 \pm 0.06\%$, which is higher than the percentage yield of biodiesel produced from the oil seeds of *Gul Mohr* 87% [16]. The kinematic viscosity of the fatty acid methyl esters corresponded to biodiesel specification for both ASTM and European Standard limits, which indicate the presence of short chain unsaturated methyl fatty acid esters and is likely to produce less deposit when burnt in combustion engines [23].

The flash point of Balsam Oil Methyl Esters (BOMEs) conforms to the ASTM and (EN 2003) for biodiesel limit. This shows that the biodiesel produced has fewer tendencies to ignite accidentally, since flashpoint is the lowest fuel temperature at which application of ignition source causes the vapor of the fuel sample to ignite under the prescribed test conditions and also a parameter used to assess the overall flammability hazard of fuel [25].

The cetane number of the Balsam Oil Methyl Esters (BOMEs) was found to correspond to the biodiesel specification for ASTM Standard limits. The higher the cetane number the better it is in its ignition properties. Biodiesel has higher cetane number than conventional diesel fuel, which results in higher combustion efficiency [26].

The pour point of the Balsam Oil Methyl Esters (BOMEs) was found to be -0.3°C . There is no standard specification for pour point due to variation in atmospheric condition.

The cloud point of Balsam Oil Methyl Esters (BOMEs) was found to be 1.1°C . Cloud point test characterizes the low temperature operability of diesel fuel. There is no standard specification for cloud point due to variation in atmospheric condition.

The specific gravity of Balsam Oil Methyl Esters (BOMEs) was found to be 0.8713 g/cm^3 this is lower than the specific gravity of biodiesel produced from *Lagenaria Vulgaris* with specific gravity of 0.8879 g/cm^3 [23]. This indicates that the biodiesel produced can be handled and stored safely. It is an important physical property in handling and storing of fuels [19].

The sulphur content of Balsam Oil Methyl Esters (BOMEs) was 0.032 ppm , and was found to correspond to the biodiesel specification for ASTM Standard limit of 0.050 ppm . This indicates that the biodiesel produced could emit less SO_x upon combustion [16].

5.0 Conclusion

The oil content of the plant seed shows economic viability of feedstock for biodiesel production and the physicochemical properties of the oil is promising with the exception of saponification and free fatty acid values which were above their limits for biodiesel production. The percentage of biodiesel production from the oil was high with more long chain methyl esters.

References

- [1] Michael, J., and Briggs, Y. (2004). ["Widescale Biodiesel Production from Algae"](#). UNH Biodiesel Group (University of New Hampshire). Archived from [the original](#) on March 24, 2006. Retrieved 2007-01-02.
- [2] Butler, R. A. (2006). Why is oil palm replacing tropical rainforests? Why are biofuels fueling deforestation? April 25, 2006. See also: http://news.mongabay.com/2006/0425 - oil_palm.html.
- [3] Nick F. and Greg A. (2008). Degumming and Bleaching : Effect on Selected Constituents of Palm Oil. *Journal of Oil Palm Research*.(16). 57-63.
- [4] Akinoso, R. and Raji A. O. (2010). “ Optimization of Oil Extraction from Locust Beans using Response Surface Methodology”. *European Journal of Lipid science and Technology* 113(2)245-252
- [5] Ajala, A. S., & Adeleke, S. A. (2014). Effect of drying temperatures on physicochemical properties and oil yield of African star apple (*Chrysophyllum albidum*) seeds. *G.J. E.D.T.*, 3(3):12-16
- [6] Andrew, C., Buba, A. A., Itodo, A. U., & Etim, E. E. (2012). Thermoxidative degradation of commonly used vegetable oils: A comparative study. *Journal of Emerging Trends in Engineering and Applied Sciences*, 3(6), 924 – 928.

[7] Fakhri, N. A., and Qadir, H. K. (2011). *Journal of Environmental Science and Engineering*, 5, 844 – 849. Fellows, P. (1998). Food processing technology: Principles and Practice. Pub. Ellis Horwood Limited, England, p. 143.

[8] Akpan, U.G., Jimoh, A., Mohammed A.D. (2006). “Extraction, Characterization and Modification of Castor Seed Oil”. *Leonardo Journal of Sciences* 8:43-52

[9] Aremu M. O., Ibrahim .H and Bamidele T. O. (2015). Physicochemical Characteristics of the Oils Extracted from Some Nigerian Plant Foods – A Review Chemical and Engineering Research. Vol. 32

[10] Mabaleha, M.B., Mitei, Y.C. and Yeboah, S.O. (2007). “A Comparative Study of the Properties of Selected Melon Seed Oils as Potential Candidates for Development into Commercial Edible Vegetable Oils.” *Journal of American Oil Chemists Society* 84:31-36

[11] Eka H. D., Aris, T.Y and Nadiah, W.A. (2010). Potential use of Malaysian Rubber (Heveabrsiliensis) Seed as Food, Feed and Biofuel; *International Food Research Journal* 17:527-534.

[12] ASAE (1999). Handbook of agricultural processing, ASAE publishers USA

[13] Younis, Y.M., S. Ghimary and S.S. Al-Shihry (2000). “African Cucurbita Pepo L. Properties of Seed and Variability in Fatty Acid Composition of Seed Oil”. *Phytochemistry* 54(1): 71-75.

[14] Fariku S., Ndonya, A. E and Bitrus, P.Y. (2007). “Biofuel Characteristics of Beniseed (sesamumindicum) Oil”. *African Journal of Biotechnology* 6(21):2442-2443

[15] Nourredini, H., Teoh, B.C and Clements, L.D. (1992). Viscosities of vegetable oils and fatty acids. *Journal of American Chemical Society*. 69:1184-1188.

[16] Edward Ntui Okey and Peggy Ari Okey (2013). Optimization of biodiesel production from non edible seeds of Delonix regia (Gul Mohr) Vol. 1, Pp 1-8

[17] Oloefe, A.U., Ibeto, C.N and Ugwuamake, I.E (2012). Determination of Optimal catalyst concentration for biodiesel yield from cocoa nut oil, Abstract of the 3rd international workshop on renewable energy for sustainable development In Africa, Enugu, pp 20.

[18] Ayoola, P. B. & Adeyeye, A. (2010). Effect of heating on the chemical composition and physico – chemical properties of *Arachis hypogea* (groundnut) seed flour and oil. *Pakistan Journal of Nutrition*, 9(8) 751 – 754.

[19] Abayeh, O.M, Garba, I.H, and Adamu H.M and Abayeh O.J (2013). Quality Characteristics of *Luffa aegyptiaca* seed oil. *International Journal of Scientific and Engineering Research*, Vol. 4, Pp 11-15.

[20] Akanni, M. S., Adekunle, A. S., and Oluyemi, E. A. (2005). Physicochemical properties of some non-conventional oil seeds. *J. of Food Technology*,3(2), 177 –181

[21] Aremu, M. O., & Akinwumi, O. D. (2014). Extraction, compositional and physicochemical characteristics of cashew (*Anarcadium occidentale*) nuts reject oil. *Asian Journal of Applied Science and Engineering*, 3, 33 – 40.

[22] VanGerpen, J., Shanks, B., Pruszko, R., Clement,D. and Knothe, G. (2004). Biodiesel analytical methods, National *Renewable Energy Laboratory SR-510-36240*, 22-56, retrieved from <http://www.osti.gov/bridge>.

[23] Sokoto, M.A., Hassan, L.G., Salleh, M.A., Dangoggo, S.M., and Ahmad, H.G. (2013). Quality Assessment and Optimization of Biodiesel from *Lagenaria Vulgaris* (Calabash) Seeds Oil. *Int. J. Pure Appl. Sci. Technol.*, 15(1) (2013), pp. 55-66

[24] Bello E.I., Anjorin S.A and Agge M. (2013). Production of Biodiesel from Fluted Pumpkin (*Telfairia Occidentalis* Hook F.) seeds Oil. Vol. 2, Pp 22-31 biodiesel market.

[2] Knothe .G, Garpen J.V., KrahJ., (2005). *Biodiesel Hand Book*, Published by AOCS, Press, Champaign, Illinois.

451 [27] Saroj K. P and Singh, R. K. (2011). Non-edible oils as the potential source for the
452 production of biodiesel in India: A review *Journal of Chemical Pharmaceutical*
453 *Research*. **3**(2), 39-49.

454